

The Hitachi Compute Blade logical partitioning (LPAR) feature brings the performance and reliability of mainframe-class virtualization to blade computing.

TRANSFORM VIRTUALIZATION ECONOMICS RELIABLE TRUSTED INNOVATE INFORMATION
GLOBAL CHANGE INTELLIGENT TECHNOLOGY SERVICES VALUE INSIGHT OPPORTUNITY
SOCIAL INFRASTRUCTURE INTEGRATE ANALYZE DISCOVER COMPETITIVE

Hitachi Compute Blade With Logical Partitioning Feature

Enable Secure, Mission-Critical Virtualization Across the Data Center

Virtualization: Get More From Less

IT departments everywhere face the challenge of diminishing budgets and increasing demand. Blade servers such as those from Hitachi Data Systems increase data center density and minimize power use, but compute and I/O resources may still be overallocated or underutilized. Virtualization technologies allow these unused resources to be put to effective use, increasing return on investment or even delaying the need to buy new equipment.

Virtualization also frees applications from the rigid boundaries of hardware. System resources can be increased to satisfy peak workloads or freed up for other applications when demand falls. When used with the Hitachi Compute Blade 2000 SMP feature, an application can even use the combined capacity of multiple blades.

All virtualization technologies are not created equal, however.

With the introduction of the Hitachi Compute Blade logical partitioning (LPAR) feature,

Hitachi Compute Blade customers benefit from decades of development work on mainframe virtualization technology. This feature brings mainframe-class virtualization to blade computing.

With flexible deployment options, high performance, security and extreme reliability, Hitachi LPAR virtualization technology firmly positions Hitachi Compute Blade as a true enterprise-class system.

Hitachi LPAR: Embedded Virtualization

Hitachi LPAR virtualization enables physical server resources to be allocated among multiple securely isolated partitions to maximize the efficiency and utilization of blade server hardware. Each logical partition hosts its own independent guest operating system and application environment.

Individual CPU cores can either be assigned to specific logical partitions for maximum security (dedicated mode), or shared between partitions for maximum utilization (shared mode).

CPU and other resources assigned to shared mode partitions can be dynamically re-allocated to allow rapid response to changes in application workload.

Fibre Channel Virtualization

Multiple logical partitions can access a shared storage device through a single Fibre Channel card, reducing the number of connections required between server and storage.

Virtual NIC

The virtual network interface card (vNIC) function allows sharing of I/O resources and enables communication between partitions without the need for physical network interface hardware.

Integrated System Management

Secure and integrated Hitachi system management software provides full visibility and management of the virtualized environment. Capabilities include dynamic allocation of resources among logical partitions without interrupting operations.

High Performance

Because embedded logical partitioning allocates system resources at the hardware level, Hitachi LPARs have a natural performance advantage over host-emulation virtualization methods. Guest operating systems are directly executed in the virtualized environment without the need for host intervention.

KEY FEATURES

High Performance

- Hardware-level resource management.
- Mainframe-style direct execution.

High Security

- Secure isolation of guest operating systems.
- Enhanced security in multitenant environments.

High Reliability

- Monitors I/O and memory requests.
- Blocks malfunctions and reports errors.

High Flexibility

- Rapid response to changing workloads with dynamic provisioning.

High Efficiency

- Optimized use of CPU and I/O resources.
- Reduced power consumption.
- Reduced floor and rack space.

High Compatibility

- Requires minimal host intervention.
- Offers higher software compatibility than host-emulation virtualization solutions.

HITACHI COMPUTE BLADE WITH HITACHI LPAR VIRTUALIZATION

System	Hitachi Compute Blade 500	Hitachi Compute Blade 2000
LPARs per Server	2-30	2-60*
Maximum (Max.) Processors per Server	4 Processors (32 Cores)	8 Processors (80 Cores)*
Max. Memory Allocation per Partition	1534.50GB	1534.50GB*
Max. I/O Allocation per Partition	2 x Mezzanine Card (CB520H, CB520A) 4 x Mezzanine Card (CB540H)	16 x PCIe, 2 x Mezzanine Card (64 x PCIe, 8 x Mezzanine in 4 Blade SMP Mode)*
Supported Guest Operating Systems	Red Hat Enterprise Linux 6.2, Microsoft® Windows® Server 2008 R2 SP1	Red Hat Enterprise Linux 6.2, Windows Server 2008 R2 SP1
Hitachi Compute Blade Management Software Features	LPAR Configuration Management, Power Control, N+1 Cold Standby, Operating System Deployment, Cloning	
Power Management Features	CPU Idle-Time Power-Saving Feature, Power Capping, NTP Time Synchronization	

* Multiblade SMP configuration

Hitachi Data Systems

Corporate Headquarters
2845 Lafayette Street
Santa Clara, CA 96050-2639 USA
www.HDS.com

Regional Contact Information

Americas: +1 408 970 1000 or info@hds.com
Europe, Middle East and Africa: +44 (0) 1753 618000 or info.emea@hds.com
Asia Pacific: +852 3189 7900 or hds.marketing.apac@hds.com



© Hitachi Data Systems Corporation 2013. All Rights Reserved. HITACHI is a trademark or registered trademark of Hitachi, Ltd. Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation. All other trademarks, service marks, and company names are properties of their respective owners.

Notice: This document is for informational purposes only, and does not set forth any warranty, expressed or implied, concerning any equipment or service offered or to be offered by Hitachi Data Systems Corporation.

DS-198-C DG April 2013